

SUPERFLEX™

Interlocked stainless steel armor (outside) and stainless steel, extra smooth liner (inside) assures highest flow rates. Standard construction is cotton packed. Other packings are available on special order.

Applications:

Pneumatic conveying of grains, powder, pellets, clay, ash, fertilizers, wood chips, drugs, chemicals, corrosive, hot or abrasive materials, and a variety of other dry products.

Characteristics:

Temp. Range: -60° F to +1800° F, depending on packing used. Std. Length: 25'

SUPERFLEX HEAVY DUTY STAINLESS STEEL

Armor Thickness: .018"
Liner Thickness: .018"
I.D. Sizes: 1½" to 16"

SUPERFLEX MEDIUM STAINLESS STEEL

Armor Thickness: .018"
Liner Thickness: .015"
I.D. Sizes: 1½" to 16"

SUPERFLEX LIGHT STAINLESS STEEL

Armor Thickness: .015"
Liner Thickness: .015"
I.D. Sizes: 1½" to 16"

GALVAFLEX™

Interlocked galvanized steel armor with a choice of stainless steel or galvanized steel liner. Standard construction is not packed.

Applications: For the transfer of a wide variety of dry bulk, hot or abrasive materials.

Characteristics:

Temp. Range: -60° F to +450° F
Std. Length: 25'

GALVAFLEX 350S

.018" Galvanized Armor with .018" Stainless Steel Liner.
I.D. Sizes: 1½" to 16"

GALVAFLEX 350C

.018" Galvanized Armor with .018" Galvanized Steel Liner.
I.D. Sizes: 1½" to 16"

GALVAFLEX250S

.018" Galvanized Armor with .015" Stainless Steel Liner.
I.D. Sizes: 1½" to 16"

GALVAFLEX 250C

.018" Galvanized Armor with .015" Galvanized Steel Liner.
I.D. Sizes: 1½" to 16"

GALVAFLEX 150S

.015" Galvanized Armor with .015" Stainless Steel Liner.
I.D. Sizes: 1½" to 8"

GALVAFLEX 150C

.015" Galvanized Armor with .015" Galvanized Steel Liner.
I.D. Sizes: 1½" to 8"

UNLINED METAL HOSE

Interlocked general purpose metal hose. Stainless steel aluminized and galvanized.

Applications: For engine intake and exhaust systems, conduit, granular materials movement, spouts, casings and chimney liners.

Characteristics:

Temp. Range: -60° F to +1800° F, depending on material specified. Std. Length: 25'

UNLINED R-600-S

Extra Heavy Duty Stainless. Strip Thickness: .030"

UNLINED R-600-G

Extra Heavy Duty Galvanized. Strip Thickness: .030"
I.D. Sizes: 2" to 16"

UNLINED R-500-S

Heavy Duty Stainless Steel. Strip Thickness: .024"

UNLINED R-500-G

Heavy Duty Galvanized. Strip Thickness: .024"

UNLINED R-500-AS

Heavy Duty Aluminized Steel. Strip Thickness: .024"
I.D. Sizes: 3" to 16"

UNLINED R-360-S

Medium/Heavy Duty Stainless. Strip Thickness: .018"

UNLINED R-360-G

Medium/Heavy Duty Galvanized. Strip Thickness: .018"

UNLINED R-360-AS

Med./Heavy Duty Aluminized Steel. Strip Thickness: .018"
I.D. Sizes: 3" to 16"

UNLINED R-300-S

Medium Duty Stainless Steel. Strip Thickness: .015"

UNLINED R-300-G

Medium Duty Galvanized. Strip Thickness: .015"
I.D. Sizes: 1" to 16"

UNLINED R-200-S

Light Duty Stainless Steel. Strip Thickness: .010"

UNLINED R-200-G

Light Duty Galvanized. Strip Thickness: .010"
I.D. Sizes: 1" to 6"

T.A. HOSE

Extra Heavy Duty or Lightweight packed hose for hot tar.

TA-600G

Extra Heavy Duty Galvanized. Strip Thickness: .030"
I.D. Sizes: 2", 3", and 4"

TA-500G

Heavy Duty Galvanized. Strip Thickness: .024"
I.D. Sizes: 2", 3", and 4"

